Approved by FITA Council on 20 August 2006 Effective as of 1 January 2007

Book 3, Article 8.2.1.3

8.2.1.3 Tolerance of Measurements

The target face will be measured using the diameter of each separate circle enclosing each of the 10 scoring zones. The tolerance of each diameter will not exceed ± 1 mm for the scoring zones 10, 9 and 8 and ± 2 mm for the other scoring zones when measured through the centre.

| Zone | Diameters in cm | | Tolerance |
|----------|-----------------|----|-------------|
| | 60 | 40 | in mm \pm |
| Inner 10 | 3 | 2 | 1 |
| 10 | 6 | 4 | 1 |
| 9 | 12 | 8 | 1 |
| 8 | 18 | 12 | 1 |
| 7 | 24 | 16 | <u>2</u> |
| 6 | 30 | 20 | <u>2</u> |
| 5 | 36 | 24 | <u>2</u> |
| 4 | 42 | 28 | <u>2</u> |
| 3 | 48 | 32 | 2 |
| 2 | 54 | 36 | 2 |
| 1 | 60 | 40 | <u>2</u> |

For the Compound Division only the inner ten (10) ring will score 10, the rest of the yellow scoring zone will score 9.

Note: Target faces printed before 1 January 2007 will be accepted

Target face, see drawing Book3, Appendix 1